

**• • R E M A R K S / A R G U M E N T S • •**

The Official Action of February 11, 2004 has been thoroughly studied. Accordingly, the changes presented herein for the application, considered together with the following comments, are believed to be sufficient to place the application into condition for allowance.

On page 2 of the Official Action the Examiner has stated that applicants' substitute specification filed 11-21-03 (November 19, 2003) has not been entered because on page 6 as seen in the marked up copy, "outer surface of the outer sheet" should be --inner surface of the outer sheet-- to be consistent with the originally filed specification.

In response to the Examiner's statement, applicants have made the correction noted by the Examiner and are resubmitting the marked-up and clean copies of the substitute specification.

It is noted that the Examiner's comments found on pages 3-4 of the Official Action concerning corrections and informalities in the specification are comments that were repeated from pages 3-4 of the Official Action of August 19, 2003. The changes made to the substitute specification filed November 19, 2003 previously addressed the comments made by the Examiner, which are now repeated on pages 3-4 of the present Official Action.

The substitute specification is being submitted under 37 CFR §1.125(b). The marked-up copy of latest version of the specification (as entered by the Examiner on August 19, 2003) shows deleted text struck-out and added text underlined.

Under the provisions of 37 CFR §1.125(b) applicants submit that the substitute specification contains only the changes shown in the marked-up copy and does not include any new matter.

Entry of the substitute specification is respectfully requested.

On page 2 of the Official Action the Examiner has stated that the drawing amendments filed 11-21-03 have not been entered, because the submitted sheets of drawings were not marked "Annotated Marked-up Drawings" in compliance with 37 CFR §1.121.

Accordingly, the proposed drawing amendments are hereby being resubmitted and have been labeled "Annotated Marked-up Drawings" in conformity with 37 CFR §1.121.

The Examiner is requested to acknowledge receipt and review and approve the proposed drawing amendment so that applicants' can proceed with having replacement drawing sheets prepared and submitted.

On page 3 of the Official Action the Examiner has objected to the drawings under 37 CFR §1.83(a) as not showing the features of the invention recited in claims 3 and 8.

In response to applicants' previous remarks on pages 8 and 9 of the Preliminary Amendment filed November 19, 2003, the Examiner has stated that applicants' comments were not persuasive because "Figure 7, a cross section along line IV-IV of Figure 2, does not show at least one groove which extends across the crotch region into the front and rear waist regions which is intersected by a second groove."

In response to the Examiner's concerns regarding the features of claim 3, claim 3 has been amended herein to delete the recitation that the at least one groove extends across said crotch region into said front and rear waist regions.

With regard to the limitations of claim 8, the Examiner has stated that "claim 8 would not require the same illustration as Figure 6, because 28 would not be shown, i.e., the pressure sensitive adhesive would be denoted differently."

Applicants submit that the only different between Fig. 6 and an illustration of a detachably fixed absorbent member would be changing reference numeral 28 to a new reference numeral to identify a pressure-sensitive adhesive. Such a change would not change the structure illustrated in Fig. 6.

Therefore, it is not believed that a separate figure is needed for the subject matter of claim 8.

The specification teaches that hot melt adhesives, pressure-sensitive adhesives and mechanical fasteners are equivalent so that one skilled in the art would not need a separate figure illustrating these equivalent means to understand applicants' invention- these equivalent means would all be located in the same area to secure the same elements together.

By the present amendment, independent claim 1 has been amended to recite that each of the at least one groove consists of a first segment that extends into the crotch region and the front end portion and a second segment that extends into the crotch region and the rear end portion, the first and second segments of each individual ones of the at least one groove being aligned with one

another longitudinally and being excluded from extending across a longitudinal center of the crotch portion of the diaper.

Support for this change to independent claim 1 can be readily found in the drawings.

It is noted that this change to claim 1 was made to more clearly recite the structure which was previously recited in claim 1. Upon reviewing the manner in which the Examiner interpreted the language of claim 1 (as stated below), it became clear that more definite language was needed to recite the previously intended structure.

Also by the present amendment, claim 2 has been changed to recite at least one groove that extends in a direction orthogonal to said longitudinal direction.

As noted above, claim 3 has been amended to delete the recitation that the at least one groove extends across said crotch region into said front and rear waist regions.

Claim 7 has been amended in the manner courteously suggested by the Examiner.

Entry of the changes to the claims is respectfully requested.

The Examiner has rejected claims 1, 2, 4, 5 and 7 under 35 U.S.C. §102(b) as being anticipated by U.S. Patent No. 2,788,003 to Morin.

Claims 3 and 6 stand rejected under 35 U.S.C. §103(a) as being unpatentable over Morin in view of the American Heritage Dictionary definition of "grid" and U.S. Patent No. 3,430,630 to Megison et al.

Claims 1 and 8 stand rejected under 35 U.S.C. §103(a) as being unpatentable over U.S. Patent No. 4,022,210 to Glassman in view of Morin and U.S. Patent No. 5,514,120 to Johnston et al.

On page 4 of the Official Action the Examiner has included a section titled *Claim Language*

*Interpretation.* Under this section the Examiner has stated:

Claim 1 now recites the at least one groove being excluded from extending longitudinally across a central crotch portion of the diaper. "Excluded" is interpreted as not being present. While a crotch region 8 has been described, the terminology "a central crotch portion of the diaper" has not been specifically defined relative to that region to specific dimensions. Therefore such terminology will be given its common meaning, i.e. some central portion of a crotch region, i.e. the at least one groove is not present at some centrally located portion of a crotch region which portion can be of any dimension.

In response to the Examiner's "Claim Language Interpretation," applicants have amended claim 1 to recite:

each of said at least one groove consists of a first segment that extends into the crotch region and the front end portion and a second segment that extends into the crotch region and the rear end portion, said first and second segments of each individual ones of said at least one groove being aligned with one another longitudinally and being excluded from extending across a longitudinal center of the crotch portion of the diaper.

Morin and Glassman (and Megison et al. and Johnston et al.) each teach absorbent articles that include groove structures that extend longitudinally across the center of their respective articles.

Applicants' independent claim 1 excludes the groove from extending longitudinally across the center of the crotch portion of the diaper.

Accordingly, the prior art of record fails to anticipate or otherwise render obvious applicants' claimed invention.

Based upon the above distinctions between the prior art relied upon by the Examiner and the

present invention, and the overall teachings of prior art, properly considered as a whole, it is respectfully submitted that the Examiner cannot rely upon the prior art as required under 35 U.S.C. §102 as anticipating applicants' claimed invention.

Moreover it is submitted that the Examiner cannot rely upon the prior art under 35 U.S.C. §103 to establish a prima facie case of obviousness of applicants' claimed invention.

It is, therefore, submitted that any reliance upon prior art would be improper inasmuch as the prior art does not remotely anticipate, teach, suggest or render obvious the present invention.

It is submitted that the claims, as now amended, and the discussion contained herein clearly show that the claimed invention is novel and neither anticipated nor obvious over the teachings of the prior art and the outstanding rejections of the claims should hence be withdrawn.

Therefore, entry of the changes to the claims and withdrawal of the outstanding rejection of the claims and an early allowance of the claims are believed to be in order.

It is believed that the above represents a complete response to the Official Action and reconsideration is requested.


If upon consideration of the above, the Examiner should feel that there remain outstanding issues in the present application that could be resolved; the Examiner is invited to contact applicants' patent counsel at the telephone number given below to discuss such issues.

To the extent necessary, a petition for an extension of time under 37 CFR §1.136 is hereby made. Please charge the fees due in connection with the filing of this paper, including extension of

Appl. No. 09/997,652  
Amdt. Dated May 14, 2004  
Reply to Office Action of February 11, 2004

time fees, to Deposit Account No. 12-2136 and please credit any excess fees to such deposit account.

Respectfully submitted,

  
Michael S. Gzybowski  
Reg. No. 32,816

BUTZEL LONG  
350 South Main Street  
Suite 300  
Ann Arbor, Michigan 48104  
(734) 995-3110

111052



- 1 -

SUBSTITUTE SPECIFICATION - MARKED-UP COPY

## DISPOSABLE DIAPER

### BACKGROUND OF THE INVENTION

RECEIVED  
MAY 24 2004  
TECHNOLOGY CENTER R3700

This invention relates to a disposable diaper for absorption and containment of excrement.

Japanese Patent Application Publication No. 1996-280739A describes a disposable diaper comprising a pants-shaped outer sheet and an absorbent panel attached to an inner surface of the outer sheet. The absorbent panel longitudinally extends across a crotch region of the outer sheet into front and rear waist regions. This absorbent panel comprises a liquid-pervious sheet, a liquid-impervious sheet and an absorbent member disposed between these two sheets. When this disposable diaper is worn by a wearer, the outer sheet which is elastically stretchable in a direction surrounding the wearer's waist region causes the absorbent panel to fit close to the wearer's body.

Japanese Patent Application Publication No. 1996-38546A describes a pants-type disposable diaper provided on an inner side of the pants with an absorbent pad structure which longitudinally extends across a crotch region of the pants into



front and rear waist regions. This absorbent pad structure comprises a liquid-pervious topsheet, a liquid-impervious backsheet and an absorbent member disposed between these two sheets. When this diaper is worn, elastically stretchable side sheets provided on the pants cause the absorbent pad structure to fit close to the wearer's body.

In diapers that generally comprise a pants-type cover member and a body fluid absorbent member attached to an inner side of the cover member, like those described in the above Publications, the absorbent member has a liquid-pervious topsheet intended to be fit to a wearer's skin, a backsheet opposed to the topsheet and an absorbent core disposed between these two sheets wherein the backsheet is covered with the pants-type cover member. When such a diaper is worn, the pants-type cover member is pressed against the backsheet of the absorbent member which is thereby pressed against a wearer's skin. In this manner, the backsheet of the absorbent member is covered with the relatively thick pants-type cover member, so air permeability of the diaper may be reduced even if an air permeable and liquid-impervious sheet is used as the backsheet. As a result, the wearer's skin against which this absorbent member is pressed may suffer from an uncomfortable stuffiness.

Such a problem may occur not only with a pants-type cover member but also with an open-type cover member.

#### SUMMARY OF THE INVENTION

It is an object of this invention to provide a disposable diaper having ~~improve~~ improved air permeability which disposable diaper comprises a cover member adapted to cover front and rear waist regions as well as a crotch region of a wearer's body, and an absorbent member adapted to be attached to an inner side of the cover member.

According to this invention, there is provided a disposable diaper comprising a cover member composed of front and rear waist regions and a crotch region and a body fluid absorbent member attached to an inner side of the cover member.

In one embodiment of this invention, the body fluid absorbent member extends in a longitudinal direction across the crotch region into the front and rear waist regions and has front and rear end portions that are fixed to an inner surface of the cover member at the front and rear end portions of the cover member. The body fluid absorbent member includes a liquid-pervious topsheet that is placed against the wearer's body, a backsheet that is placed against the inner surface of the cover

member and a body fluid absorbent core disposed between these two sheets. A side of the absorbent core facing the backsheet is formed with a plurality of grooves that are concaved in a direction extending from the backsheet toward the topsheet. The grooves extend in one of the longitudinal direction and a direction that is orthogonal to the longitudinal direction.

#### BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a perspective view showing one embodiment of a disposable diaper according to this invention;

Fig. 2 is a partially cutaway plan view showing the disposable diaper as having been unfolded;

Fig. 3 is a sectional view taken along a section line III - III in Fig. 2;

Fig. 4 is a sectional view taken along a section line IV - IV in Fig. 2;

Fig. 5 is a sectional view taken along a section line V - V in Fig. 2 that is not partially cutaway;

Fig. 6 is a sectional view taken along a section line VI - VI in Fig. 2;

Fig. 7 is a sectional view similar to that in Fig. 4 but showing another embodiment of this invention;

Fig. 8 is a plan view similar to that in Fig. 2 but showing still another embodiment of this invention;

Fig. 9 is a sectional view taken along a section line IX - IX in Fig. 8; and

Fig. 10 is an enlarged sectional view showing a part of Fig. 9.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Details of a disposable diaper according to this invention will be more fully understood from the description given hereunder with reference to the accompanying drawings.

A disposable diaper 1 shown in Fig. 1 in a perspective view is of a pants-type and comprises a pants-type cover member 2 adapted to cover a wearer's waist regions and crotch region and a body fluid absorbent member 3 attached to an inner side of the cover member 2. The cover member 2 is composed of a front waist region 6, a rear waist region 7 and a crotch region 8 positioned between these two waist regions 6, 7. The front and rear waist regions 6, 7 are overlaid upon and joined to each other along transversely opposite side edge portions 11, 12, at a plurality of joining zones 13 arranged intermittently in a longitudinal direction of the diaper 1 along the respective side edge

portions 11, 12. Such diaper 1 has a waist-opening 10a and a pair of leg-openings 10b of which respective peripheral edge portions are provided with elastic members 22, 23 (See Fig. 2 also) as indicated by chain lines.

Fig. 2 is a plan view of the diaper 1 in which the side edge portions 11, 12 connecting the front and rear waist regions 6, 7 to each other have been separated from one another with the diaper 1 having been unfolded in opposite directions as indicated by arrows 14, 15 in Fig. 1. In the diaper 1 unfolded in this manner, the cover member 2 has an hour glass shape and comprises an inner sheet 16 and an outer sheet 17 which are identical in shape as well as in size and which are intermittently bonded to each other by means of appropriate adhesive such as a hot melt adhesive or a welding technique. Elastic members 22 associated with the waist-opening and elastic members 23 associated with the respective leg-openings are attached under tension to an inner surface of ~~either of the~~ inner sheet 16 or an inner surface of the outer sheet 17 along longitudinally opposite end portions 18, 19 of the front and rear waist regions 6, 7, and along transversely opposite side edge portions 21 of the crotch region 8, of the cover member 2 respectively. The absorbent member 3 extends longitudinally

across the crotch region 8 into the front and rear waist regions 6, 7 of the cover member 2 and has front and rear end portions 26, 27, which are bonded to the end portions 18, 19 of the front and rear waist regions 6, 7 by means of a hot melt adhesive 28 (See Fig. 6). Alternatively, the front and rear end portions 26, 27 can be detachably attached to end portions 18, 19 by other means such as a pressure-sensitive adhesive or a mechanical fastener well known under the trade name of ~~MAGICTAPE®~~ MAGICTAPE. Transversely opposite side edge portions 29 of the absorbent member 3 extending between the front and rear end portions 26, 27 are provided with leak-barrier cuffs 31 which have openings toward a transversely middle zone of the absorbent member 3. Elastic members 33 extending between the front and rear end portions 26, 27 are attached under tension to inner edge portions 32 of the leak-barrier cuffs 31. The absorbent member 3 is, as indicated by chain lines in Fig. 2, formed on its backsheet 37 with a first ~~groove~~ grooves 41 (See Fig. 4).

Figs. 3 through 5 are sectional views taken along section lines III - III, IV - IV and V - V extending in the transverse direction, respectively, in Fig. 2, with Fig. 5 not being cutaway as is Fig. 2. Referring to Fig. 3 which shows the

diaper 1 in a sectional view taken along the section line III - III extending across the crotch region 8 and bisecting the diaper 1 into front and rear halves, the absorbent member 3 comprises a liquid-pervious topsheet 36 destined to contact with the wearer's skin, the previously described backsheet 37 which is preferably liquid-impervious and destined to contact with the inner sheet 16 of the cover member 2, and a body fluid absorbent core 38 disposed between the top- and backsheets 36, 37. The core 38 contains hydrophilic fibers 61 and superabsorbent polymer particles 62 and longitudinally extends toward the front and rear end portions 26, 27 of the absorbent member 3 and has a rectangular shape. The top- and backsheets 36, 37 extend outwardly beyond a peripheral edge of the core 38 and are joined together in a water-tight manner using an appropriate adhesive or a welding technique. Along the opposite side edge portions 29 of the absorbent member 3 the backsheet 37, which is joined with the topsheet 36, extends outwardly beyond the side edges of the topsheet 36 and the extensions of the backsheet 37 are folded inwardly in the transverse direction of the absorbent member 3 forming the respective leak-barrier cuffs 31. Portions of these leak-barrier cuffs 31 lying on the front and rear end portions 26, 27 of the absorbent member 3 are joined to these

front and rear end portions 26, 27 using an adhesive 40 or a welding technique. In a state in which the absorbent member 3 is longitudinally curved in a U-shape configuration (See Fig. 1), contraction of elastic members 33 associated with the leak-barrier cuffs 31 causes the leak-barrier cuffs 31 to rise and form openings 39 which are oriented toward the transversely middle zone of the absorbent member 3. In this transversely middle zone, the backsheet 37 is bonded to an inner surface of the cover member 2 by means of adhesive 30.

Now referring to Fig. 4 which shows the diaper 1 in a sectional view taken along the section line IV - IV which is ~~nearer~~ nearer to the rear waist region 7 than the section line III - III which divides the diaper 1 into front and rear sections as viewed in the longitudinal direction as indicated in Fig. 2, the absorbent member 3 is formed on the side of the backsheet 37 with a pair of first grooves 41 (See Fig. 4) that are concaved toward the topsheet 36 and extend longitudinally toward the front and rear end portions 26, 27. Each of the first grooves 41 preferably has a width of about 2 - 20 mm and a depth corresponding to about 1/4 - 3/4 of the thickness of the core 38, and each of the first grooves 41 has an inner side that is lined with the backsheet 37. The core 38 is disposed between



the backsheet 37 which defines the inner side of the respective first grooves 41 and the topsheet 36 which is opposed to the backsheet ~~36-~~ 37. The first grooves 41 are intended to maintain clearance spaces between the absorbent member 3 and the member 2, which clearance spaces serve to improve permeability of the diaper 1 even when these members 2, 3 are brought into a close ~~contact-~~ contact with one another.

Referring to Fig. 5 which shows the diaper 1 in a sectional view taken along the section line V - V extending in the transverse direction along the end portion 19 of the cover member 2 as indicated in Fig. 2 (without the cutaway portion), the portions of the top- and backsheets 36, 37 extending outwardly beyond the peripheral edge of the core 38 are overlaid and bonded to the cover member 2 using an adhesive 42 or a welding technique. It is also possible to attach these overlaying top- and backsheets 36, 37 in a detachable manner to the cover member 2 using an appropriate means such as pressure-sensitive adhesive.

Referring to Fig. 6 which shows the diaper 1 in a sectional view taken along the section line VI - VI extending between the front and rear end portions 18, 19 of the cover member 2 as indicated in Fig. 2, each of the first ~~groove~~ grooves 41 ~~is~~ are

separated respectively in the crotch region 8 in the longitudinal direction by an appropriate spacing. If necessary, it is also possible to form all of the first grooves 41 so that they are connected and continuous, rather than being separated in the longitudinal direction. It should be understood that, while the leak-barrier cuffs 31 are normally folded down onto the topsheet 36, the leak-barrier cuffs 31 are illustrated in Fig. 6 as being raised somewhat in order that the presence of these leak-barrier cuffs 31 can be ~~apparently recognized.~~ seen.

When the diaper 1 of such a structure is worn, the cover member 2 and the absorbent member 3 are maintained in a spaced apart relationship from each other along the first grooves 41 even when these members 2, 3 are brought into a close contact with each other. Accordingly, air permeability between the interior and the exterior of the absorbent member 3 can be improved. For example, an air permeable and liquid-impervious sheet may be used as a stock material for the backsheet 37 of the absorbent member 3 to ensure that a flow of air high in temperature and humidity can be guided from the interior of the core 38 through the backsheet 37 into the first grooves 41 and freely moved therein without being hindered by the cover member 2. With the inner and outer sheets 16, 17 of the cover member 2

being air permeable, a flow of air high in temperature and humidity introduced into the first grooves 41 can be exhausted therefrom ~~into the exterior~~ outside of the diaper 1.

Fig. 7 is a view similar to Fig. 4 but showing another embodiment of the invention. The absorbent member 3 of this embodiment of the diaper 1 is formed with, in addition to the first grooves 41 extending in the longitudinal direction, a pair of second grooves 46 extending in the transverse direction, i.e., orthogonally to the first grooves 41, between the transversely opposite side edge portions 29 of the absorbent member 3. These second grooves 46 facilitate ~~the flow of~~ that is high in temperature and high in humidity to be ~~exhausted~~ vented from the first grooves 41 and thereby the air permeability of the absorbent member 3 is further improved. Preferably, one or more portions of the second grooves 46 having substantially the same dimensional width and depth as the first grooves 41 may intersect one portion of the first grooves 41.

Fig. 8 is a view similar to Fig. 2 but showing still another embodiment of the invention, Fig. 9 is a sectional view taken along the section line IX - IX in Fig. 8 and Fig. 10 is an enlarged sectional view showing a portion of Fig. 9. The diaper 1 shown in Figs. 8 - 10 has, in addition to the first grooves 41

or both the first and second grooves 41, 46 which are formed in the absorbent member 3 on the side of the backsheet 37, third grooves 47 formed in the absorbent member 3 on the side of the topsheet 36 so as to extend in the longitudinal direction. Preferably, the absorbent member 3 is formed on the side of the topsheet 36 with at least one portion of the third grooves 47 having an appropriate length and more preferably with at least two portions of the third grooves 47 each being spaced apart in the longitudinal direction in the crotch region 8 of the cover member 2. Referring to Fig. 8, the absorbent member 3 is formed along each of its transversely opposite side edge portions 29 with a pair of the third grooves 47 spaced from each other in the longitudinal direction. Taking account of the fact that the presence of the third grooves 47 tends to, in the same manner as the first grooves 41 in the embodiment shown by Fig. 4, restrain the absorbent member 3 from being easily curved between the front and rear end portions 26, 27, it is preferred to separate each of the third grooves 47 in the crotch region 8 so that the absorbent member 3 may be easily curved and thereby facilitated to fit to the wearer's crotch region. Each of the third grooves 47 preferably has a width of about 2 - 20 mm and a depth corresponding to about 1/4 - 3/4 of the thickness of the core

38. The third grooves 47 formed in this manner can reduce an amount of body fluids permeated sideways and prevent body fluids from leaking sideways of the diaper 1 by introducing body fluids such as urine to be guided thereinto.

As is apparent from Fig. 10 which shows the diaper 1 in an enlarged sectional view, the position of the third grooves 47 substantially conforms to the position of the first grooves 41 as viewed in the transverse direction of the diaper 1. With the first and third grooves 41, 47 formed in the absorbent member 3 on the side of the backsheet 37 and the side of the topsheet 36, respectively, in such an alignment, the absorbent member 3 can be curved as indicated by imaginary lines in Fig. 10 to follow a contour of the wearer's waist as the diaper 1 is worn. The first grooves 41 are deformed with their widths widened and the third grooves 47 are deformed with their widths narrowed as the absorbent member 3 follows the contour of the wearer's waist in the waist-surrounding direction. Such deformation of the grooves 41, 47 advantageously allows the absorbent member 3 to follow the contour of the wearer's waist without the formation of wrinkles on the side of the topsheet 36 even if the core 38 has a thickness of about 10 - 20 mm. Therefore, there is no apprehension that the presence of the topsheet 36 might cause

the wearer to experience an uncomfortable feeling. In this way, the first grooves 41 which serve to improve the air permeability of the absorbent member 3 are preferably positioned with respect to the third grooves 47 so that the ability of the absorbent member 3 to fit around the wearer's waist may also be improved. More specifically, with the first grooves 41 and the third grooves 47 positioned with respect to one another as illustrated in Fig. 10, it is preferred to dispose the core 38 between the first and third grooves 41, 47 so that body fluids can be dispersed in the absorbent member 3 in the transverse direction through the core 38.

While the present invention has been described hereinabove with respect to a pants-type disposable diaper as the typical embodiment thereof, the invention is also applicable to an open-type disposable diaper. The cover member 2 may be formed from a nonwoven fabric or plastic film both of which are preferable. The core 38 of the absorbent member 3 may be formed from fluff pulp fibers 61 and superabsorbent polymer particles 62. The superabsorbent polymer particles 62 may be mixed with the fluff pulp fibers 61 and this mixture may be layered in the thickness direction of the core 38. The superabsorbent polymer particles 62 may be distributed so as to have a density that gradually

increases in a direction that extends from the topsheet 36 toward the backsheet 37. The Figure 9 illustrates how the distribution density of the superabsorbent polymer particles 62 may be varied in the transverse direction of the absorbent member 3. For example, as shown in ~~referring to~~ Fig. 9, the distribution density of the superabsorbent polymer particles 62 may be adjusted to be higher in a lower zone of the absorbent core 38 defined between a pair of the first grooves 41 than in an upper zone of the absorbent core 38 located above the lower zone. In any case, an amount of the superabsorbent polymer particles 62 used to form the core 38 is preferably about 2 - 98 % by weight of the core 38. Thermoplastic synthetic fibers having a melting point of  $100^{\circ}\text{C} \pm 20^{\circ}\text{C}$  may be mixed into the core material up to 20 % by weight to facilitate formation of the first - third grooves 41, 46, 47 by heating the core 38 under pressure.

The disposable diaper according to this invention has the first grooves and the second grooves formed in the absorbent member 38 on the side of the backsheet which is attached to the inner side of the cover member. The grooves contribute to improvement of air permeability of the absorbent member itself as well as to the air permeability between ~~this~~ the absorbent

member and the cover member so that no stuffiness ~~may occur even~~  
is felt when the absorbent member is closely in contact with the  
wearer's skin.